A80

Android Desktop Terminal

Android OS 6.0 | 3G, WiFi, Bluetooth 4-Inch Capacitive Touchscreen | 0.3 Megapixel Front Camera | Thermal Printer | NFC Contactless | PCI PTS 5.x, SRED | Optional Camera and Battery Backup

A80, Versatile, Portable & Robust

PAX A80, the most cost-effective in the A-series is versatile enough to work as a countertop or indoor portable device (given the optional backup battery).

Leverage a world of Android-based apps to get more for your business, and always run at peak performance.

Full connectivity means the A80 is a reliable workhorse that will process payments safely and fast, even during the busiest hours.

4-inch touchscreen display and multiple network connectivity, A80 delivers the best user experience to the modern consumers.



FEATURES & BENEFITS

Unprecedented Security

- Ultra-Safe Security Processor
- NFC Contactless Certified
- Supports RSA, AES, 3DES Micro
- SD Expandability
- PCI PTS 5.x, SRED

Exceptional Performance

- Inbuilt 0.3 Megapixel Front Camera (optional)
- 3G, WiFi, Bluetooth, Dial, Ethernet PayDroid
- Powered by Android 6.0
- Optional Battery Backup
- Capacitive Touchscreen



SPECIFICATIONS

OS	PayDroid Powered by Android 6.0
05	, , ,
Processor	Application CPU: Quad-core Cortex-A53, 1.2GHz Security CPU: Cortex M3
Memory	1GB DDR + 8GB eMMC 1 x Micro SD Card Slot, Supports up to 32GB
Card Readers	Magnetic Card Reader Smart Card Reader Contactless Card Reader
Camera	0.3 Megapixel Fixed Focus Front Camera (optional) Reads 1D & 2D Codes
Display	4-Inch Colour Display 800 x 480 Pixels Capacitive Touchscreen
Audio	1 x Speaker
Physical Keypad	10 x Numeric Keys 5 x Function Keys Back-Lighting
Communications	3G WiFi (2.4G) Dial (PSTN) LAN Bluetooth 4.0
Card Slots	3 x SAM I 1 x SIM + 2 x SAM
Peripheral Ports	1 x HOST USB 2.0 1 x Micro USB 2.0, OTG 1 x PINpad 1 x RS232 1 x LAN 1 x Line 1 x Phone
Printer	High-Speed Thermal Printer Print Speed: 90mm/s Paper Width: 58mm Paper Diameter: 50mm
Battery	7.4V / 720mAh Rechargeable Li-ion Battery (optional)
Adapter	Input: 100 - 240V AC, 50Hz / 60Hz Output: 9.0V DC, 1.0A
Accessories	Cluster Cable (optional) Privacy PIN Shield (optional) Battery Backup (optional)
Physical	L x W x H (mm) : 181 x 84 x 81 Weight (g) : 405 (Excluding Battery)
Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature 10% ~ 93% Relative Humidity, Non-condensing -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature
Certifications	PCI PTS 5.x, SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless American ExpressPay Discover D-PAS IC MasterCard TQM Interac_Flash L2 J/Speedy L2 UL CE FCC RoHs





www.paxtechnology.com

This document is provided to you for informational purposes only. all features and specifications are subject to change without notice. PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. All other trademarks or brand names are the properties of their respective holders. Copyright 2018, PAX Technology Limited, All Rights Reserved.

